

Important guidelines for the installation of a Dr. Jekyll & Mr. Hyde exhaust system

1. Connect the electronic components as indicated on the labels of the cables.
2. Find an appropriate spot to put the servo motor, under the seat is usually enough room
3. Cut the outer cables at the right length
4. Attach the outer and inner cable to the servo motor, pull the inner cable and tighten the M3 screw
5. By pushing the horn button you can try if the valves of the system open and close easily
6. If this doesn't work properly, unscrew the M3 screw on top of the servo motor to give the inner cable a little more room and make sure that you tighten the M3 screw again
7. Caution!!! Make sure that the outer cable doesn't touch the exhaust or catalyst because it will melt and get damaged beyond repair.

Good luck and have fun with your electronically adjustable exhaust system !

The Jekyll & Hyde Installation Service

When there is no Dr. Jekyll & Mr. Hyde dealer near you, we are more than willing to install your electronic adjustable exhaust system onto your motorcycle for a reasonable fee. This will take place in our service workshop in Belfeld and takes, depending on the brand and model, about 2 to 3 hours. In our workshop we also solve possible problems during and after the warranty period (2 years). Make an appointment and we will make sure there is fresh coffee and 'vlaai' (a traditional pie from the Province of Limburg in the southern part of the Netherlands) while you wait.

If you want to extend your stay and have a wonderful weekend in Limburg we will make reservations at a hotel near the river Maas.